

Li-Ion 18650 Rechargeable Battery 1200MAH Wired With BMS

slug: li-ion-18650-rechargeable-battery-1200mah-wired-with-bms



TECHNICAL SPECIFICATIONS & SUMMARY

[Lithium Battery Cell] Li-Ion 18650 Rechargeable Battery 1200MAH Wired With BMS Li-Ion Rechargeable Battery Nominal Specifications : Standard discharge capacity : Min. 1200mAh Nominal voltage : 3.63 V Maximum charge voltage : 4.20 V Standard charge current : CCCV, 1.3A, 4.20V, 20mA or 3hr cut-off Charging time Standard charge : 180min (@ RT) Rapid charge : 150min (@ RT) Max. continuous discharge : 1.2A (@ RT) Discharge cut-off voltage : 2.75V (End of discharge) Cell weight : 38.0g max (Approx) Cell dimension Height : Max. 65.00 mm Diameter : Max. 18.4 mm Operating temperature (Cell Surface temperature) Charge : 0 to 45 Discharge: -10 to 60 Colour may Be different from Picture shown Please ensure the standard precautions while using Li-ion cells to not puncture or damage the cells. Also please ensure that the charging and discharging parameters and temperatures are maintained within the specifications for achieving the longer cell life and optimal performance.

UNIT PRICE (EX. GST)

Rs. 69

WITH 18% GST

Rs. 81

In stock: 10 units - HSN: 85423100

Order online at uniksystem.in or email Unik.systems98@gmail.com for bulk pricing.