

TDT 10S 20A NMC Battery Protection and Charger BMS with Balance Hardware

slug-for-10s-20a-nmc-battery-protection-and-charger-bms-with-balance-hardware



TECHNICAL SPECIFICATIONS & SUMMARY

TDT BMS NMC 10S 20A WITH BALANCE Hardware Product Data Sheet The BMS NMC 10S 20A WITH BALANCE (TDT) is a robust and efficient Battery Management System designed for 10-series (10S) lithium-ion NMC battery packs. With a nominal system voltage of 37V and a continuous current capacity of 20A, this module ensures safe and stable operation of high-performance battery packs used in e-mobility, energy storage, and industrial tools. Technical Specifications Battery Chemistry: Lithium-ion (NMC) Configuration: 10S (10 cells in series) input Voltage B+ to B-: -0.3~+20V Overcharge Detection voltage/1CELL: 4.28+/-0.05V Over discharge Detection voltage/1CELL: 2.8+/-0.1V Over current: 4-6A Suggest working temperature: -20 deg C~+60 deg C Key Features 20A High Current Support Perfect for mid-to-high power battery packs used in electric bikes, scooters, power tools, and solar inverters. Built-in Balancing Function Automatically maintains uniform voltage across all cells to extend overall battery life. Comprehensive Protections Protects against overcharge,

UNIT PRICE (EX. GST)
Rs. 649

WITH 18% GST
Rs. 766

In stock: 0 units - HSN: 85423100
Order online at uniksystem.in or email Unik.systems98@gmail.com for bulk pricing.